



Code: Q/NW 2851

Edition: A

FCY-EGIV Aircraft Deicing/Anti-icing Fluid (SAE Type IV) Instruction

Chengdu P.R. China

NEWAVE AEROCHEMICAL Co., Ltd.

目录

1. Introduction	3
2. Product name	3
3. Chemical Structure Formula	3
Not Applicable	3
4. Physicochemical Properties	3
5. Specification of Quality	3
5.1 Carried Standard	3
5.2 Technical Data	3
5.3 Package And Standard	3
5.4 Shelf Life	3
5.5 Product Discard Disposal Method	3
6. Main Materials	3
7. Uses And Usage	3
8. Storage And Transportation Conditions	4
9. Fire, Explosion, Shock, Radiation And Corrosion Measures	4
10. Service	4
11. Other Information	4

1. Introduction

FCY-EGIV Aircraft Deicing/Anti-icing Fluid is an ethylene glycol-based Type IV fluid containing water, corrosion inhibitors, wetting agents, thickeners and green dye. It is formulated to be used neat (undiluted) as an anti-icing fluid for extended protection time against precipitation. The fluid has been tested in accordance with SAE International (SAE) Aerospace Material Specification (AMS) 1428/1 and has been fully qualified.

2. Product name

FCY-EGIV Aircraft Deicing/Anti-icing Fluid (SAE Type IV)

3. Chemical Structure Formula

Not Applicable.

4. Physicochemical Properties

pH (20°C)	7.8 ±0.5 (ASTM E70)
Refractive Index (20°C)	1.3906± 0.0015 (ASTM D1747)
Specific Gravity(20°C)	1.080±0.015(ASTM D891)
Flash Point	No flash to 100°C(ASTM D93)
Freezing Points	-43.0±3°C(neat)

5. Specification of Quality 5.1

Carried Standard

AMS 1428K

5.2 Technical Data

Appearance	green liquid
Viscosity Limits	27000~42000(#31 spindle, 0.3 rpm, 0°C)
Lowest on-wing viscosity (LOWV)	24800 mPa.s(#34 spindle, 0.3 rpm, 0°C)
Maximum on-wing viscosity (MOWV)	43700 mPa.s(#31 spindle, 0.3 rpm, 0°C)
Lowest Operational Use Temperature (LOUT)	-29°C

5.3 Package And Standard

Plastic barrel.

210kg/Drum, 1050kg/IBC.

5.4 Shelf Life

2 years under correct storage and sealed.

5.5 Product Discard Disposal Method

All disposal should be carried out in accordance with state and local requirements.

6. Main Materials

Ethylene glycol, Water, Thickener, Surfactant, Corrosion inhibitor.

7. Uses And Usage

Uses: FCY-EGIV for de-icing and anti-icing of aircraft surfaces in winter ice, snow and frost

conditions.

Usage: FCY-EGIV is to be used neat (undiluted). Please observe the MH/T 3011.19 standard and the de-icing and anti-icing methods provided by the aircraft manufacturer for different types of aircraft, and refer to the latest de-icing information issued by the relevant international organizations when using it.

Note:

- 1) Do not mix aircraft de/anti-icing fluids of different manufacturers and different trademarks.
- 2) It is recommended to take the necessary labor protection measures when using FCY-EGIV.
- 3) To lessen shear degradation, use diaphragm pumps in loading and unloading. Keep away from contaminated and exposed to ultraviolet light when stored. Having any questions, please contact with us.
- 4) To ensure proper use, the user has any questions about this product, please contact us.

8. Storage And Transportation Conditions

- a. **Packing mark:** Each batch of products should have a quality inspection report, and there should be clear and firm marks on the packaging bag, including product trademark, name, lot number, net weight, implementation standard and so on.
- b. **Storage:** Store in a cool and airtight place, away from direct sunlight and ultraviolet rays. It is strictly prohibited to store with oxidizing, acidic, alkaline, corrosive and other substances.
- c. **Storage and handling:** It is a stable chemical product, non-corrosive, non-flammable, non-explosive, suitable for various forms of transportation.

9. Fire, Explosion, Shock, Radiation And Corrosion Measures

Not applicable

10. Service

- a. If the customer has any objection to the receipt of the products, it shall raise the objection within one month after the receipt of the products, and both parties shall settle the matter through negotiation. Unsealed products, our company does not do quality assurance
- b. If you have any other questions, please contact us.

11. Other Information

In the normal operation conditions, if the consumers comply with the instruction provided by the manufacturer, the product does no damage to aircraft materials

Company: NEWAVE AEROCHEMICAL Co., Ltd

Address: No.17 South Section 2nd Ring Road Chengdu P.R.

Postcode: 610041

Telephone: 028-82909323, 85236817, 82909889;

Website: www.newave.cn;

Fax: 028-85218402

E-mail: marketing@newave.cn